



DINO-POWER


NINGBO DINO-POWER MACHINERY CO.,LTD.

Add: Fanshidi Industry District, Jiangshan Town, Yinzhou, Ningbo, China.

Tel: +86-574-88278841, 88278851

WeChat/WhatsApp: +86-13566005805

WeChat/WhatsApp: +86-18858210064



DINO-POWER

Dedicated In Painting

www.dpairless.com



2023

NINGBO DINO-POWER MACHINERY CO.,LTD.

Certificate



Factory



THE X SERIES.

These high-performance and heavy-duty electric airless paint sprayers are designed for sustained operation on a wide variety of projects, from a single room in a house to a warehouse or manufacturing facility. The X Series electric airless sprayers are durable with jobsite features that keep contractors spraying.



X DINO-POWER AIRLESS SPRAYER X6

Easy Pressure Control

Easy Pressure Control with user-friendly symbols for simple selection of operating modes from low pressure cleaning, medium pressure rolling, and high pressure airless painting .

Portable and light weight

Convenient and Lightweight with built-in carrying handle, easy to take, and easy to store.

Piston Pump

Powerful Piston Pump offers modular components, easy maintenance and less problem.

Replaceable worn parts

The piston rod, O-rings, gasket etc. Worn parts could be replaced which will save your maintenance cost.

Includes:

1/4"x7.5M high pressure hose, X-450 spray gun, 30cm extension pole, 517 X airless tip and



Enjoy your painting,
and enjoy your life !

DP-X6V
with 5L hopper



DP-X6



Pump Repair Kits

Spring Seal & S.S Rod prolong the lifetime.

The High Quality Valves

With high grade Stainless Steel Tungsten Carbide, Ceramic ball ensure the durability

Optional Accessories



DP-637PR

The 637PR Paint Roller

The paint roller and Straight gun are optional which can be used for refurbishment without any splashing.

it easy for DIY homeowners and handymen to finish the medium size project with speed and finesse. The high-pressure pump delivers a finely atomized spray for a flawless professional finish. It will be one full series based on that.



DP-X6H

Battery-driven Airless Paint Sprayer with High Cart Battery-driven Road Line Striper Electric Air-mix Airless Paint Sprayer with High Cart Electric Airless Paint Sprayer with Cart & 5L Hopper It will be one full series based on that.

Airless Field Striper



DP-X6L
Gas/Battery drive

Item No.	DP-X6 DIY	DP-X6H with a 5L hopper	DP-X6L high-trolley	DP-X6L Line Striper
Pressure controlling	Mechanical	Mechanical	Mechanical	Mechanical
Motor power	650W	650W	650W	Mechanical
Flow rate	1.4L/min	1.4L/min	1.4L/min	48V/20Ah
Max. tip size	0.019"	0.019"	0.019"	0.019"
Max. pressure	200bar/2900psi	200bar/2900psi	200bar/2900psi	200bar/2900psi



AIRLESS SPRAYER X9



X9 sprayers make it easy for DIY homeowners and handymen to finish the medium-size project with speed and finesse.

The high-pressure pump delivers a finely atomized spray for a flawless professional finish.

Advantage	Compact size, professional finish easy to step, use and clean.
Project	Small-to-midsize household projects such as doors, trim, interior walls and ceilings, decks and fences, and houses.
Material	Interior paint, varnish, oil-based paints, primer, chalk paint, wood preservative staining products
Specification	- Motor 700w - Flow rate 1.5LPM - Max. Tip size 0.019" - Max. Pressure 3000Psi
Max. Viscosity	Handles all standard paints without diluting in most cases (for smooth substrates and particularly high-viscosity, gel-like paints, dilute in 10% increments)

ACCESSORIES



Pump Repair Kits
S.S. Piston rod prolong the lifetime
DP-X9RK Piston rod & Packings



High quality Valves
With S.S. Tungsten Carbide, Ceramic ball ensure the durability
DP-X9VK Inlet&Outlet, prime/spray valve.



High Pressure hose and Connector
DP-637H05 1/4x7.5M High Pressure hose*
DP-637C 1/4x1/4 Connector



Extension Pole
Attached to spray gun to extend your reach
Ideal for spraying ceilings, overhangs and decks
DP-637LT15 15cm DP-637LT30 30cm*
DP-637LT 50 50cm DP-637LT75 75cm



Lubricating oil
Daily use to protect pump rod and packings
DP-637LO 150ml*



Filters&Strainers
Remove unwanted debris and reduce tip clogs.
DP-637F60 60-mesh Gun Filter
DP-637F100 100-mesh Gun Filter*
DP-637SF40 40-mesh inlet strainer*



Airless Spray Tip
Professional finish
Reversible-clear tip clogs quickly with just a twist
DP-637XT 517*



X Tip Guard
7/8 in thread fits all regular spray gun
DP-637SX*



Tip Gasket
For use with latex and solvent-based materials.
DP-637G*
*Mark means the standard size along with machine

1

**ON/OFF Switch
Pressure Control**
Match your project - slow to fast!

Stable pressure for different size tips

Light Weight Gun
Comfort trigger

5

Compact stand with
cable winder

7.5M High
pressure hose

2

Lubrication Hole
Protect Piston Rod
And Packings

3

Spray directly
from a 5L or 20L
container

4

Aluminum pump body
stainless steel valve,
carbide and ceramic
wear parts

Replaceable Worn Parts
Extends sprayer life.

NEW! | AIRLESS SPRAYER |



External fuse for easy Maintenance



Running indicator light for troubleshooting





MAXIMIZE YOUR INVESTMENT WITH THE X SERIES.

Dino-power is committed to providing the best quality electric airless sprayers.

All sprayers are 100% factory-tested and field-proven.


Our mission is to fit you to the sprayer that is sized for the work you do to get the job done right, every time.



X Design Of Appearance/
Lacquered Outer Shell
The flat, smooth and bright external surfaces and beautiful shape.
Available on all X models.



Electric Pressure Control
The Microprocessor programmed to perform at maximum efficiency for each tip size ensuring a consistent spray pattern at all pressure settings.
Available on models X24-81L, T60/T85



Brushless Motor
The Brushless Motor never wears, No brushes or commutator to wear out. No sparking from carbon brush High torque, Low amp draw, Longer cords
Available on models X24-81L, T60/T85



Manifold Filter Housing
The filter bowl is hand tight so access requires no tools. Pressure relief valve made for long duty life and reliability. The positive shut off that results means you're always ready to spray.



Chrome Plated Steel Tubing
Enormously strong and tough Chromium plated for durability

Available on models X20-X81L



Pneumatic-Tyre
For no-flat reliability. To absorb impact and add greater mobility on the job site.

Available on models X20-X81L High Cart



High Quality Drive Train
Germany bearings. High efficiency, quieter operation Run in synthetic grease Positive heat transfer for longer bearing and gear life

Available on models X24-81L, T60/T85



High Quality Fluid Pump
Carbide blend used for ball and seat Ensures positive shut off

Available on models X24-81L, T60/T85



High Capacity Tool Box
It's storage box for easy carry the accessories like the gun, tips, guards, filters, tools and lubricating oil etc

Available on models with high cart.



The Hanger For Side Lay
The hanger is able to support the machine during reloading the material, and can also be used for hose reel during storage.

Available on models with high cart.



+ HC6 Material Hopper
Convert your unit to this Hopper for smaller jobs that do not require as much paint Less cleanup and gravity feed helps to assure your unit stays primed with material when using small amounts of paint

Available on models X20-X32



+ HCa60 Material Hopper
The 60L gravity feed hopper for high production painting and plastering applications.

Available on models X51L-X81L T60-T85



Small Size. Large Capability. Built with the same quality as the Large Electric sprayers, TheSmall Electric airless sprayers deliver exceptional power and performance.

Features:

High Quality Drive Train
Hardened steel gears provider quieter operation and longer bearing and gear lifetime



HC6-24
6L Material Hopper for smaller jobs that do not require as much paint

Durable Piston Pump
Long life V-packings, Piston Rod and hardened stainless steel cylinder lasts longer

High Torque DC Motor
Fan-cooled DC motor, you get reliable performance every day.



Electric Airless Sprayer

The X20 is a entry- level machine, Recommended for small and medium residential and commercial projects.it's a compatible piston pump for Airless beginners



Includes:
X-450 Airless Spray Gun, 517# Airless tip, 1/4X15M High pressure hose, 45cm extension pole, Lubricating oil, O-rings*2(For suction hose) Cable ties*2



Notes:
The HC6-24 material hopper is optional.

	X20
SPECIFICATIONS	
Motor Power	1100w
Motor type	PMDC
Max. Flow Rate	2.0L/min
Max. Tip size	0.021"
Max.Working pressure	200Bar
Weight	16kgs

Cordless Airless Sprayer

The X20C is light weight and makes it easier to move and transport, Stop wasting time dealing with long extension cords, Setup where you want instead of where the power is located, Consistent, all-day spraying power without power fluctuations.



Includes:
X-450 Airless Spray Gun, 517# Airless tip, 1/4X15M High pressure hose, 2*20V 5.0Ah Battery, Charger, 45cm extension pole, Lubricating oil, Manual. O-rings*2(For suction hose) Cable ties*2



Notes:
The 220v to 38v adapter is optional, which can be used as a normal corded machine.

	X20C
SPECIFICATIONS	
Voltage	40V
Battery	10.5Ah
Motor power	600w
Motor type	PMDC
Max. Tip size	0.021"
Max.Working pressure	200Bar



High performance cordless paint sprayer Supports up to 227 bar with 0.021 inch max tip. Sprays up to 45 mins continuous working on a fully charged battery(Using 517# tip @ 150Bar). Expanded application capability to spray anywhere!

Features:

Cordless & High Performance
All the performance of a corded X20 along with the freedom from power cords, electrical outlets or generators. Experience the power and freedom to spray every job faster



Durable Piston Pump
Long life V-packings, Piston Rod and hardened stainless steel cylinder lasts longer

Large Battery Capacity
45-minutes of runtime when used with 517 @ 150 Bar spraying pressure



Adjustable Pressure Control
Delivers an extended battery run time when spraying at low pressure.



X20i includes all features from the X20

Features:



Electric Pressure Control
Constantly monitors performance and adjusts motor speed to match your tip size and spraying needs

Full sized Mainfold Filter
Easy maintenance and less clogging.



Durable Piston Pump
Long life V-packings, Piston Rod and hardened stainless steel cylinder lasts longer

Lacquered Outer Shell
The flat, smooth and bright external surfaces and beautiful shape.

Electric Airless Sprayer

The X20i is ideally suited for residential, property maintenance and small commercial applications. This high performance electric airless sprayer will apply all standard architectural primers, paints and coatings efficiently.



Includes:
X-450 Gun, 517# tip, 1/4X15M hose, 45cm extension pole, Lubricating oil,17-19 &19-22 Double open end wrench, Cross screwdriver O-ring*2 (For suction hose)Cable ties*2



Notes:
The HC6-24 material hopper is optional.

SPECIFICATIONS	X20i(H)
Motor Power	1100w
Motor type	PMDC
Max. Flow Rate	2.0L/min
Max. Tip size	0.021"
Max.Working pressure	200Bar
Weight	16kgs

Electric Airless Sprayer

The X24/X28(H) are midsize electric airless sprayers make it easier to get more work done in a day with increased flow and production rates.



Includes:
X-450 Gun, 517# tip, 1/4X15M hose, 45cm extension pole, Lubricating oil,17-19 &19-22 Double open end wrench, Cross screwdriver

	X24(H)	X28(H)
SPECIFICATIONS		
Motor Power	1300w	2200w
Motor type	Brushless Motor	Brushless Motor
Max. Flow Rate	2.4L/min	2.8L/min
Max. Tip size	0.023"	0.025"
Max.Working pressure	227Bar	227Bar
Weight	16kgs	17kgs

Notes:
The HC6-24 material hopper is optional.



The X24/X28(H) are mid-size electric sprayers increased productivity &Unmatched reliability.

Features:

Maintenance-Free Brushless Motor
Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure.



Easy To Handle
Compact design for ease of transport and space-saving storage
Also available as High-Cart



Lacquered Outer Shell
The flat, smooth and bright external surfaces and beautiful shape.



Recommended for medium and some large residential, commercial and industrial projects.

Features:

Electric Pressure Control
Constantly monitors performance and adjusts motor speed to match your tip size and spraying needs



Full sized Mainfold Filter
Easy maintenance and less clogging.

Durable Piston Pump
Long life V-packings, Piston Rod and hardened stainless steel cylinder lasts longer



Electric Airless Sprayer

The X32&X40 continues the climb to increased performance. This mid-range unit is perfect for residential, property maintenance, rental, and light commercial applications and is equipped with digital technology for improved efficiency.



Includes:
X-450 Gun, 517# tip, 1/4X15M hose, 45cm extension pole, Lubricating oil, 17-19 & 19-22 Double open end wrench, Cross screwdriver O-ring*2 (For suction hose)Cable ties*2



	X32	X40
SPECIFICATIONS		
Motor Power	2600w	2800w
Motor type	Brushless	Brushless
Max. Flow Rate	3.5L/min	4.0L/min
Max. Tip size	0.031"	0.035"
Max. Working pressure	227Bar	227Bar
Weight	21kgs	23kgs



Includes:
X-450 Gun, 517# tip, 1/4X15M hose, 45cm extension pole, Lubricating oil, 17-19 & 19-22 Double open end wrench, Cross screwdriver



	X32H	X40H
SPECIFICATIONS		
Motor Power	2600w	2800w
Motor type	Brushless	Brushless
Max. Flow Rate	3.5L/min	4.0L/min
Max. Tip size	0.031"	0.035"
Max. Working pressure	227Bar	227Bar
Weight	36kgs	38kgs



Maintenance-Free Brushless Motor
Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure.



High Capacity Tool Box
It's storage box for easy carry the accessories like the gun, tips, guards, filters, tools and lubricating oil etc

Easy To Handle
Compact design for ease of transport and space-saving storage
Also available as High-Cart



Large Pneumatic Tires
To absorb impact and add greater mobility on the job site.



Recommended for applications using up to 2 guns for texture and high build coatings.

Features:

Submerged Fluid Section

The submerged foot valve creates the most efficient suction system on the market today, which handles heavy bodied coatings with ease

Built with carbide balls and seats that are resistant to abrasive coatings



Electric Pressure Control

Constantly monitors performance and adjusts motor speed to match your tip size and spraying needs

Durable Piston Pump

Long life V-packings, Piston Rod and hardened stainless steel cylinder lasts longer



Electric Airless Sprayer

The X51L is perfect for contractors that need a durable and dependable sprayer for level 5 finishes; knockdown texture and high build coatings.



Includes: DP-6376G Gun, 521&531# tip, 3/8X15M hose, 45cm extension pole, Lubricating oil, 17-19 & 19-22 Double open end wrench, Cross screwdriver Monkey wrench(0-30mm&6-68mm), 3/8"(F)x3/8"(M) Swivel Connector



Notes: The HC-60 Material hopper is optional.

SPECIFICATIONS		X51L
Motor Power		3000w
Motor type		Brushless Motor
Max. Flow Rate		5.0L/min
Max. Tip size		0.037"
Max. Working pressure		227Bar
Weight		48kgs



Includes: DP-6376G Gun, 531&541# tip, 3/8X15M hose, 45cm extension pole, Lubricating oil, 17-19 & 19-22 Double open end wrench, Cross screwdriver Monkey wrench(0-30mm&6-68mm), 3/8"(F)x3/8"(M) Swivel Connector



Notes: The HC-60 Material hopper is optional.

SPECIFICATIONS		X81L
Motor Power		4500w
Motor type		Brushless Motor
Max. Flow Rate		8.0L/min
Max. Tip size		0.045"
Max. Working pressure		227Bar
Weight		52kgs



Recommended for applications using up to 2 guns in large residential, commercial and industrial projects.

Features:

Maintenance-Free Brushless Motor

Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure.



The support hanger

The support hanger is able to support the machine during reloading the material, and can also be used for hose reel during storage.

High Capacity Tool Box

It's storage box for easy carry the accessories like the gun, tips, guards, filters, tools and lubricating oil etc



Large Pneumatic Tires

To absorb impact and add greater mobility on the job site.



Recommended for applications using up to 2 guns for texture and high build coatings.

Features:

Submerged Fluid Section

The submerged foot valve creates the most efficient suction system on the market today, which handles heavy bodied coatings with ease

Built with carbide balls and seats that are resistant to abrasive coatings

Electric Pressure Control

Constantly monitors performance and adjusts motor speed to match your tip size and spraying needs



60L Material Hopper

The 60L gravity feed hopper for high production painting and plastering applications.



Electric Airless Sprayer
(Static V-Packing Design)

The T60&T85 is perfect for contractors that need a durable and dependable sprayer for level 5 finishes; knockdown texture and high build coatings.
*With Static Packing Design, No need for a wearable cylinder which means the lower maintenance cost



Includes:
DP-6376G Gun, 521&531# tip, 3/8X15M hose, 45cm extension pole, Lubricating oil, 17-19 & 19-22 Double open end wrench, Cross screwdriver Monkey wrench(0-30mm&6-68mm), 3/8"(F)x3/8"(M) Swivel Connector



Notes:
The HC-60 Material hopper is optional.

SPECIFICATIONS	T60
Motor Power	3000w
Motor type	Brushless Motor
Max. Flow Rate	6.0L/min
Max. Tip size	0.037"
Max. Working pressure	227Bar
Weight	48kgs



Includes:
DP-6376G Gun, 531&541# tip, 3/8X15M hose, 45cm extension pole, Lubricating oil, 17-19 & 19-22 Double open end wrench, Cross screwdriver Monkey wrench(0-30mm&6-68mm), 3/8"(F)x3/8"(M) Swivel Connector



Notes:
The HC-60 Material hopper is optional.

SPECIFICATIONS	T85
Motor Power	5000w
Motor type	Brushless Motor
Max. Flow Rate	8.5L/min
Max. Tip size	0.045"
Max. Working pressure	227Bar
Weight	52kgs




Recommended for applications using up to 2 guns in large residential, commercial and industrial projects.

Features:

Maintenance-Free Brushless Motor

Due to the improved performance, the motor works even more efficiently at low and also at high speeds. The continuous paint pressure measurement controls the motor speed automatically, thus ensuring a constant material pressure.



The support hanger

The support hanger is able to support the machine during reloading the material, and can also be used for hose reel during storage.

High Capacity Tool Box

It's storage box for easy carry the accessories like the gun, tips, guards, filters, tools and lubricating oil etc



Large Pneumatic Tires

To absorb impact and add greater mobility on the job site.



X SERIES.
THE CONTRACTOR CHOICE FOR ELECTRIC
AIRLESS PAINT SPRAYERS



	X20	X20C	X20i	X24	X24H	X28	X28H	X32
Max. tip size	0.021"	0.021"	0.021"	0.023"	0.023"	0.025"	0.025"	0.031"
Flow rate	2.0L/MIN	2.0L/MIN	2.0L/MIN	2.4L/MIN	2.4L/MIN	2.8L/MIN	2.8L/MIN	3.2L/MIN
Max.Working pressure	200bar/2900psi	200bar/2900psi	200bar/2900psi	227bar/3300psi	227bar/3300psi	227bar/3300psi	227bar/3300psi	227bar/3300psi
Motor Power	1100W	1100W	1100W	1300W	1300W	2200W	2200W	2600W
Power Source	Corded	40V 10.Ah atteries B	Corded	Corded	Corded	Corded	Corded	Corded
Cart Design	Stand	Stand	Stand	Stand	High-Cart	Stand	High-Cart	Stand
2 Guns Support	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2 Guns 0.021"
Pressure controlling	Mechanical	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Digital Display	N/A	N/A	Y	Y	Y	Y	Y	Y
Motor	PMDC	PMDC	PMDC	Brushless DC	Brushless DC	Brushless DC	Brushless DC	Brushless DC
Max. Hose Length	90M	90M	90M	90M	90M	90M	90M	90M
Power Cord Length	2M	2M	2M	2M	2M	2M	2M	2M
Net/Gross weight	14.9/20.1kgs	14.9/20.1kgs	14.9/20.1kgs	15.1/20.3kgs		16.4/21.6kgs		17.8/22.5kgs
Gun Included	X-450	X-450	X-450	X-450	X-450	X-450	X-450	X-450
Reversible Tip Included	517	517	517	517	517	517	517	517
Airless Hose Included	1/4"*15M	1/4"*15M	1/4"*15M	1/4"*15M	1/4"*15M	1/4"*15M	1/4"*15M	1/4"*15M
Accessories Included	45cm extension pole, Lubricating oil O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver O-rings*2(For suction hose) Cable ties*2
Package	Carton box (49*42*54)	Carton box (49*42*54)	Carton box (49*42*54)	Carton box (49*42*54)	Carton box (64*58*85)	Carton box (49*42*54)	Carton box (64*58*85)	Carton box (50*42*58)
20'FT Loading Qty	260 SETS (28.9CBM)	260 SETS (28.9CBM)	260 SETS (28.9CBM)	260 SETS (28.9CBM)	100 SETS (30.9CBM)	260 SETS (28.9CBM)	100 SETS (30.9CBM)	176 SETS (26.6CBM)



X32H	X40	X40H	X51L	X81L	T60	T85
0.031"	0.035"	0.035"	0.037"	0.045"	0.037"	0.045"
3.2L/MIN	4.0L/MIN	4.0L/MIN	5.0L/MIN	8.0L/MIN	6.0L/MIN	8.5L/MIN
227bar/3300psi	227bar/3300psi	227bar/3300psi	227bar/3300psi	227bar/3300psi	227bar/3300psi	227bar/3300psi
2600W	2800W	2800W	3000W	4500W	3000W	5000W
Corded	Corded	Corde d	Corded	Corded	Corded	Corded
High-Cart	Stand	High-Cart	High-Cart	High-Cart	High-Cart	High-Cart
2 Guns 0.021"	2 Guns 0.023"	2 Guns 0.023"	2 Guns 0.025"	2 Guns 0.031"	2 Guns 0.025"	2 Guns 0.031"
Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Y	Y	Y	Y	Y	Y	Y
Brushless DC	Brushless DC	Brushless DC	Brushless DC	Brushless DC	Brushless DC	Brushless DC
90M	90M	90M	90M	90M	90M	90M
2M	2M	2M	2M	2M	2M	2M
			52.4/67kgs	56/70.6kgs	52.4/67kgs	56/70.6kgs
X-450	X-450	X-450	DP-6376G(3/8" Inlet)	DP-6376G(3/8" Inlet)	DP-6376G(3/8" Inlet)	DP-6376G(3/8" Inlet)
517	517	517	525&531	531&541	525&531	531&541
1/4"*15M	1/4"*15M	1/4"*15M	3/8"*15M	3/8"*15M	3/8"*15M	3/8"*15M
45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver O-rings*2(For suction hose) Cable ties*2	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver Monkey wrench(0-30mm) Monkey wrench(6-68mm) 3/8"(Fx3/8"(M) Swivel Connector	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver Monkey wrench(0-30mm) Monkey wrench(6-68mm) 3/8"(Fx3/8"(M) Swivel Connector	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver Monkey wrench(0-30mm) Monkey wrench(6-68mm) 3/8"(Fx3/8"(M) Swivel Connector	45cm extension pole, Lubricating oil 17-19 Double open end wrench 19-22 Double open end wrench Cross screwdriver Monkey wrench(0-30mm) Monkey wrench(6-68mm) 3/8"(Fx3/8"(M) Swivel Connector
Carton box (64*58*85)		Carton box(64*58*85)	Carton box with Pallet (68*66*89)	Carton box with Pallet (68*66*89)	Carton box with Pallet (68*66*89)	Carton box with Pallet (68*66*89)
100 SETS (30.9CBM)		100 SETS(30.9CBM)	63 SETS(25.1CBM)	63 SETS(25.1CBM)	63 SETS(25.1CBM)	63 SETS(25.1CBM)

Airless Piston Pumps



**Mechanical
pressure control**

Durable and reliable

Quality proven fluid pump

Stainless steel fluid section is durable, light weight and rust proof; could be used for both water-based and also oil-based paint. Also, Innovation design makes it easy for putting/ removing siphon swivel into/from lower inlet housing

Quality proven fluid pump

Stainless steel fluid section is durable, light weight and rust proof; could be used for both water-based and also oil-based paint. Also, Innovation design makes it easy for putting/ removing siphon swivel into/from lower inlet housing

Quality v-packing & piston rod

Teflon+Leather v-packings & hardened Stainless steel piston rod for long lifetime spraying.



DP-6318
DP-6320

Portable carry type

Portable airless sprayer with built-in carrying handle. It's ideal for one gun residential and maintenance applications.

Chromed cart

Chrome trolley with telescoping handle & hose wrap, included with bigger wheels, Quick & easy maneuverability.

PMDC motor

Powerful permanent magnet DC motor for strong power.



DP-6318H
DP-6320H



DP-6336iB

The High Pressure Filter

It is easy to disassemble and quick to clean.

The microprocessor pressure control

The microprocessor control system will ensure the consistent fan and constant spraying pressure with low pulse and tight pressure dead band (5%). Just set your desired pressure easily, and the microprocessor will generate the fast response when spraying.

Automatic Speed Adjustment

When the paint finished in the tank, the microprocessor will reduce the speed of the motor, for reducing the wear of the piston rod & V- packing.



DP-6336iB



TEFC/Brush less Motor

The brushless motor is more powerful, durable and reliable, no carbon brush and no spark during the spraying, the oil paint or the flammable paint will be no problems.

Semi-automatic Oiler

You only need to press the Oiling button everyday before spraying, the machine will be self-lubricated and it will absolutely prolong the sprayer's lifetime and with less parts replacing/repairing.



DP-6337iB

TWO Guns available

2 guns is available at the same time for the painting job, with higher efficiency.

The Enhanced Fluid Pump Design

The low suction valve will be suitable for the high viscosity material. Such as putty spraying.

Item No.	DP-6318	DP-6318H	DP-6320
Pressure controlling	Mechanical	Mechanical	Mechanical
Motor power	1.3HP 1000W	1.3HP 1000W	1.8HP 1400W
Max. pumping capacity	1.8L/min(0.47GPM)	1.8L/min(0.47GPM)	2.2L/min(0.58GPM)
Max. tip size	0.019"	0.019"	0.023"
Max. pressure	210bar/3040psi	210bar/3040psi	210bar/3040psi

Item No.	DP-6336i	DP-6337i
Pressure controlling	Electronical+Digital display	Electronical+Digital display
Motor power	3.3HP 2500W brushless	3.3HP 2500W brushless
Max. pumping capacity	6.0 L/min(1.58GPM)	7.0 L/min(1.85GPM)
Max. tip size	0.037"	0.043"
Max. pressure	210bar/3040psi	210bar/3040psi

Triple filter system

3-steps Filtering system(Suction, manifold and gun filters) will reduce the tip clogs and ensure a quality finish.

PMDC motor

Powerful permanent magnet DC motor for strong power.

The Mechanical+Digital pressure display.

The pressure gauge shows the accurate pressure during the spraying.
And the digital display is optional.(For DP-6321i&DP-6325i)



U-Cart is optional

EzControl

Our EzControl system will ensure you consistent fan and constant spraying pressure with low pulse and tight pressure dead band (5%). Just set your desired pressure easily, and the microprocessor will generate the fast response when spraying.



DP-6321
DP-6325

Big volume output

Big volume spraying capacity support large tip size, high efficiency for large painting job.

Digital Pressure control& display

The accurately spraying pressure and paint volume display for easy operation.

The Enhanced Fluid Pump Design.

The low suction valve will be suitable for the high viscosity material. Such as putty spraying.



Quality proven fluid pump

.Stainless steel fluid section is durable, lightweight and rust proof; could be used for both water-based and also oil-based paint.
Also, Innovation design makes it easy for putting/ removing siphon swivel into/from lower inlet housing



DP-6331i

Portable carry type

Portable airless sprayer with built-in carrying handle. It's ideal for one gun residential and maintenance applications.

Chrome coated trolley with Pneumatic tyre

For easy moving and transportation.



DP-6331ip

Item No.	DP-6321(H)	DP-6321i(H)	DP-6325(H)	DP-6325i(H)
Voltage/frequency	230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ
Pressure controlling	Mechanical	Electronical	Mechanical	Electronical
Motor power	1.7HP 1300W	1.7HP 1300W	1.8HP 1400W	1.8HP 1400W
Max.pumping capacity	2.2L/min(0. 58GPM)	2.2L/min(0. 58GPM)	2.4L/min(0.63GPM)	2.4L/min(0. 63GPM)
Max.tip size	0.023"	0.023"	0.025"	0.025"
Max.pressure	210bar/3040psi	210bar/3040psi	210bar/3040psi	210bar/3040psi

Item No.	DP-6331i	DP-6331iP	DP-6335i
Pressure controlling	Electronical+Digital display	Electronical+Digital display	Electronical+Digital display
Cart type	high cart type	four-feet carry type	
Motor power	2.4HP 1800W	2.4HP1800W	2.6HP 2000W
Max.pumping capacity	3.8L/min(1.0GPM)	3.8L/min(1.0GPM)	5.0L/min(1.32GPM)
Max.tip size	0.031"*1gun	0.031"*1gun	0.035"*1gun
	0.021"*2guns"	0.021"*2guns"	0.023"*2guns
Max.pressure	210bar/3040psi	210bar/3040psi	210bar/3040psi



ELECTRIC DIAPHRAGM Airless Paint Sprayer

X AIRLESS DIAPHRAGM PUMP



DP-970iB



DP-980C



DP-960C

Brushless Motor

Powerful brushless motor and big diaphragm surface for perfect usage with high viscosity materials.

Soft-start

Smart soft-start function to protect the motor and gear box for a long life time.

Low Pressure Airless Innovation

Innovative low-pressure airless technology achieves up to 55% less over spray.

Item No.	X960C	X980C	X970iB
Pressure controlling	Mechanical	Mechanical	Mechanical
Motor power	1600W Brushless Motor	2500W Induction motor	2500W Induction motor
Flow rate	3.0L/min	4.5L/min	3.5L/min
Max.tip size	0.025"	0.031"	0.025"
Max.Working pressure	220bar/3190psi	220bar/3190psi	220bar/3190psi
Net/Gross weight	25.5/30kgs	23.36/31kgs	16.5/22kgs
Means	62x38x52.5cm	62x38x52.5cm	62x37.5x42.5cm

Compact Size

Trolley and wheel design for easy moving around for demanding construction site use.

Easy Maintenance

Service, cleaning and maintenance directly on the job site is no problems.

Professional Crack Injection

When combined with hopper and injection nozzle, it becomes perfect for precise concrete repair and injection.



X980

High Delivery Capacity

Reliable powerful induction motor generates high delivering capacity, suitable for everyday use on all residential and commercial painting projects.

Easy Maintenance

Service, cleaning and maintenance directly on the job site is no problems.

Compact Size

Trolley and pneumatic wheel design for easy moving around for demanding construction site use.

Affordable Price

Durable & Reliable performance at quite affordable price.

Variety of Coatings

Suitable for spraying varnish, color ant, latex paint, emulsion, primers, and other common water-based/oil-based coatings.

Optional with Hopper for injection and repair jobs.



X990

Item No.	X980	X990
Pressure controlling	Mechanical	Mechanical
Motor power	1500W Induction Motor	2000W Induction Motor
Flow rate	3.6L/min	4.0L/min
Max.tip size	0.023"	0.025"
Max.Working pressure	220bar/3300psi	220bar/3300psi
Net/Gross weight	34/41KGS	31/38KGS
Means	67×52×57cm	67x52x57cm



DP-7000
4.2hp 7.0L

High delivery capacity

Extreme duty airless paint sprayer with diaphragm pump system. Reliable powerful induction motor, generate high delivering

capacity, specially designed to be used everyday on all residential, industrial, and commercial project. Capable of supporting two guns spraying and long distance painting.

Easy maintenance

The diaphragm can be repalced within 15 mins

Gravity & Suction 2 in 1 Could be used in both Suction type (suction tube attached already) or Gravity type (Hopper cup is available with extra cost)

Item No.	DP-6860E	DP-6000	DP-7000
Pressure controlling	Mechanical	Mechanical	Mechanical
Motor power	2200W Induction motor	2400W Induction motor	3000-3200W Induction motor
Flow rate	4.5L/min	6.0L/min	7.0L/min
Max. tip size	0.025"	0.031"	0.042"
Max.Working pressure	220bar/3300psi	250bar/3630psi	210bar/3050psi
Net/Gross weight	37.93/40.87kgs	50/53KGS	90/101kgs
Means	67x52x57cm	67x53x54.5cm	120x75x65cm



DP-6000



DP-6860E
3.0hp 4. 5L

Pneumatic Airless Paint Sprayer



Proven quality of mechanical reverser system.

High quality pneumatic airless paint sprayer with reliable Mechanical transducer / reverser, quick action and no ice low air consumption. Provides higher efficiency & minimum maintenance, for industrial usage.



Built-in air filter group

Equipped with air filter regulator & lubricator for easy air controlling, filtering, and lubricating. Surely prolong the machine's lifetime and performance.

Large manifold filter

The large manifold filter will always ensure you equal and nice finishing without pressure fluctuate. Mean whilereducethe tip clogging also.

Pneumatic big wheels

The inflating pneumatic wheels for easy moving on rugged

Durable v-packings

Teflon + Leather V-packings will always works like new, only replace it once per year. Save you time and money on your maintenance and repairing.

Stainless steel fluid pump

K301 use Hardened stainless steel fluid pump and stainless steel piston rod, could be used for both oil-based and water-based coating.

Model No.	DP-K301	DP-K151	DP-K451
Fluid pressure ratio	30:1	15:1	45:1
Max. paint delivery (L/min)	6(1.585gpm)	12(3.17gpm)	5(1.32gpm)
Cylinder diameter	153mm		
Max. Pump Speed	100 cycles per min		
Stroke(mm)	100		
App. Air consumption at 6 bar	200-400L/min		
Air Compressor Pressure	5-8 bar		
Maximum Discharge	240bar	120bar	360bar
Air Inlet (inch)	1/4		
Fluid Outlet(inch)	3/8		
NW(kgs)	31.5kgs/69.3lbs	33kgs/72.6lbs	30kgs/66lbs

Compact size and light weight

Small size and light weight, ideal for furniture painting, factory, steel structure, etc. Commercial or industrial painting jobs which last 12 hours every day.



X-Pro Series Pneumatic Pump

Advanced Displacement Pump

Dual piston rod design.
Rapid check valve action results in minimal pulsation.
Easy servicing with multipurpose wrench.
One-point dis-assembly.
Energized seal design ensures long seal life and
Reversible valve seats offer double operating life time.



XPRO-451



XPRO-681

Advanced technology, high performance

The working performance of this new and improved X-PRO series equipment is outperformed than other pumps in their class. More durable and many models and pressure ratios are available for all of your painting demands.

X-PRO pump with many air motor sizes and different pressure ratios to choose, to improve productivity, reduce costs and lower emissions, meet all your strict requirements for painting jobs

Model No.	XPRO-451	XPRO-681
Fluid pressure ratio	45:1	68:1
Max. Delivery/min (liter)	16	9
Max. Delivery/cycle (cc)	180	250
Air Motor Effective Diameter (mm)	254	254
Max. Max. pressure (Bar)	315	476
Air pressure (Bar)	3-7	3-7
Stroke (mm)	120	120
NW/GW (kgs)	64/131	64/131
Meas	72x79x135cm	72x79x135cm



DP-6C

DP-9C

DP-6391A/B/C

Applications

DP-6C could spray thick heavy duty anti-corrosive paint, waterproofing coatings and other conventional oil-based paint.

DP-9C could spray Inorganic zinc coatings, epoxy zinc-rich primer, enamel, fire-resistant coating, other water and oil based paint.

	DP-6C	DP-9C
pressure ratio	65:1	33:1
Paint delivery(L/min)	12	24
Inlet pressure(MPa)	0.4-0.6	0.4-0.6
Air consumption(L/min)	250-2400	100-1000
Cylinder diameter(mm)	Φ240	Φ240
Dimension(mm)	520×430×670	460×430×920
Net weight(kg)	45	55



	DP6391A			DP6391B			DP6391C		
Fluid pressure ratio	30:1	45:1		38:1	46:1	69:1	45:1	60:1	76:1
Max. paint delivery (L/min)	8.4	7		13.5	10.4	7	13.5	11	8
Free load delivery (L/min)	20.8L	13.8L		33L	20.8L	13.8L	33L	22L	15L
Cycle per Liter	12	14		7	10	14	7	9	12
Cycle per gallon	48	57		29	40	57	29	36	50
Max. Pump Speed	100 cycles per min			100 cycles per min			100 cycles per min		
Air Motor Effective Diameter (mm)	200	200		250	250	250	280	280	280
Stroke (mm)	100	100		100	100	100	100	100	100
App. Air consumption at 5bar (L/min)	450	450		650	650	650	900	900	900
Air Compressor Pressure Range (bar)	3-6	3-6		3-6	3-6	3-6	3-6	3-6	3-6
Noise Level (dBa)	75	75		75	75	75	75	75	75
Maximum Discharge pressure (bar)	180	270		228	276	414	270	360	456
Air Inlet (inch)	1/4	1/4		3/4	1/2	3/4	3/4	3/4	3/4
Fluid Outlet (mm)	8	8		8	8	8	8	8	8
NW (kgs)	55	55		67	64	64	79	76	73
GW (kgs)	75	75		87	84	84	99	96	93
Packing size	65×70×110cm			65×70×110cm			65×70×110cm		
Can 2-guns spraying sametime?	yes	no		yes	yes	no	yes	yes	no

GAS

Airless Paint Sprayers & Hydraulic Pumps



EZ pressure control system
delivers a consistent spray fan without pressure fluctuations
at all spraying pressures.



DP-7900
(Engine Power) 8.3L Max.0.048"

DP-7900E
(Electric Power) 8.0L Max.0.047"



HONDA



DP-7900 TX

- Adjustable pressure control 0-3650psi / 250bar.
- Powered by 6.5hp 0-3300psi/227bar
- Telescoping handle with hose wrap, Quick easy maneuverability.
- Pneumatic tires for easy transportation on rugged construction job-site.
- Could be used for indoor / outdoor panting, acrylics, enamels, latex, primer, floor painting, fire-proofing etc. From medium to high viscosity.

Submerged Fluid
Section



Model No.	DP-7900	DP-7900E(Electric)	DP-7900TX
Suction system	normal	normal	low suction
Engine power	6.5HP 4875W	4.0HP 3000W	6.5HP 4875W
Max. pumping capacity	8.3L/min (2.19GPM)	8.0L/min (2.19GPM)	8.3L/min (2.19GPM)
Max. nozzle size	0.048"	0.047"	0.048"
Max. pressure	227bar / 3300psi	227bar / 3300psi	227bar / 3300psi
Guns support	"1gun 0.048"	"1gun 0.047"	"1gun 0.048"
	" 2guns 0.035"	" 2guns 0.033"	" 2guns 0.035"
	" 3guns 0.027"	" 3guns 0.025"	" 3guns 0.027"
	" 4guns 0.023"	" 4guns 0.021"	" 4guns 0.023"

X-Pro Series Hydraulic Pump

Direct Drive Motor/Engine



The telescopic handle

The adjustable height telescopic handle makes for convenient transport on the building site or in the car.

DP9800E/DP-9900E

Multiple Choice

380 V electric drive or independent of mains. electricity with the Honda petrol Engine are optional



P9800G/DP-9900G

Heavy-Duty Hydraulic System

Faster, more responsive changeover O-ring sealed toeliminate leaks High-precision pressure control No hydraulic reset button needed Durable hydraulic lines for long life



HONDA

Belt Dirven Motor /Engine Hydraulic Sprayers



HONDA

The Practical Swing cart

It is possible to swing up the pump: when working from a bucket or a container but also for transport.



DP-9600G



DP-9600E

Multiple Choice

380 V electric drive or independent of mains. electricity with the Honda petrol Engine are optional

Item No	DP-9800E	DP-9600E	DP-9800G	DP-9600X70(7900
Driven	Electric+hydraulic	Electric+hydraulic	Gasoline+hydraulic	Gasoline+hydraulic
Transmission	Direct	Belt	Direct	Belt
Motor power	3.75KW	3.75KW	5.5KW	5.5KW
Voltage/Frequency	380V 50Hz	380V 50Hz	HONAD or LUDWIG	HONAD or LUDWIG
Flow rate	10.0L/MIN	10.0L/MIN	12.0L/MIN	12.0L/MIN
Max. tip size	0.049"	0.049"	0.052"	0.052"

Gas Hydraulic Sprayer

For high production professional contractors who spray the wide range of materials.



DP-GH6834



HONDA

Long life Fluid Pump

Proven design and performance
Long life rod and sleeve delivers unmatched durability and life
Easy Change Pump System and quick Intake Valve eliminates downtime

High-Efficiency Cooling System

Large 15L hydraulic reservoir
Return line hydraulic filter extends life
No special hydraulic fluid needed
Quality assured cooler and blower system
Easy to use drain plug

Heavy-Duty Hydraulic System

Faster, more responsive changeover O-ring sealed
toeliminate leaks High-precision pressure control
No hydraulic reset button needed
Durable hydraulic lines for long life


500Bar Hydraulic Sprayer

Heavy-strength Frame

Easy-roll tubed pneumatic tires
Enamel painted steel tubing –corrosion protection
Multi-function design converts to skid mount in seconds

Honda Engine Or Diesel motor

13 HP Honda engine with integrated fuel tank to deliver maximum performance
Contractor preferred engine with Oil Alert
Back-up Pull Start
High-capacity, 12 Volt 18 Amp Charging System



DP-GH6934

For Protective and Intumescent Coatings

Heavy-Duty Construction
Extremely high durability and performance
Long-life seal and leather packings
Durable hydraulic lines for long life

Item No.	DP-GH6833	DP-GH6934
Driven	Gasoline+Hydraulic	Gasoline+Hydraulic
Transmission	Belt	Belt
Motor power	9KW 13HP	9KW 13HP
Voltage/Frequency	"3-phase 380V/ HONDA engine"	"3-phase 380V/ HONDA engine"
Flow rate	15-20L/min	8L/min
Max. tip size	0.065"	0.053"
Max.Working pressure	275bar/4000psi	500bar/7250psi
Oil Motor	Taiwan Oil Motor	Taiwan Oil Motor
Gross weight	195/235kgs	195/235kgs
Meas	115x80x135cm	115x80x135cm



Airless Road Line Striper

Diaphragm Pump



DP-980LR



DP-990L



DP-990LGB

Item No.	DP-980LR	DP-980L	DP-990L2
Engine power	5.5HP Honda	5.5HP Honda	5.5HP Honda
Max. pressure	250Bar/3625Psi	250Bar/3625Psi	250Bar/3625Psi
Max. flow rate	3.0L/min	3.0L/min	4.0L/min
Max. tip size	0.025"	0.025"	0.029"
Guns	One	One	Two
Net weight	62/91kgs	75/100kgs	90/115kgs
Carton size	106*64*68cm	106*71*88cm	106*71*88cm

- Operator spraying controls are located right at the handle bars, designed for more comfortable and better control.
- You can fine tune the striping system operation without stopping
- Provides easier “up to the curb” parking lot striping ,and With the Front wheel LOCK system, you can also stripe arcs and curves in any angle.
- High-comfort handle-bar design for greater striper control and less operator fatigue
- Tall, low friction easy-roll wheels in big size, push easily for less operator fatigue.
- The valves are precised machined in stainless steel + tungsten carbide material for long life.

Airless Road Line Striper

PISTON PUMP

It's the preferred choice with line striping parking lots, athletic fields. It is ideal for most low to medium VOC, waterborne traffic paints. This is a great entry level Gas engine powered striper, and can be used for small to medium sized parking lots, runways, roads marking, paths and sports fields.



HONDA



2023
NEW!

X24L

Standard package include 1 gun +1 hose



DP-6335LGB

Standard package include 2 guns + 2 hoses


- Proven durable Piston Pump with Long-life V-packings,and stainless piston rod.
- Easy operate, easy control, and easy turn in any direction.
- Fluid section has slower-stroking piston, slower cycle rate and larger displacement for longer performance life.
- Ideal for most low to medium viscosity, waterborne traffic paints.
- Versatile gun bracket can be positioned to spray on left, right, front or rear of striper.
- Ideal fro small to medium-size line marking projects on athletic fields and pavement, parking lots, roads marking etc.

Item No.	DP-6325L	DP-6335L-(A)(GB)	DP-6335L-GB	DP-6335L-A
Type	Walk-behind	Walk-behind	Walk-behind & Glassbeads dispenser	Walk-behind & Automatic
Engine power	5.5HP(HONDA)	5.5HP (HONDA)	5.5HP (HONDA)	5.5HP (HONDA)
Max. pressure	210bar / 3045psi	210bar / 3045psi	210bar / 3045psi	210bar / 3045psi
Max. flow rate	2.0L/min (0.5GPM)	4.0L/min (1GPM)	4.0L/min (1GPM)	4.0L/min (1GPM)
Max. tip size	0.023" * 1gun	0.021" * 2guns	0.021" * 2guns	0.021" * 2guns
Guns	one gun (standard)	two guns (standard)	two guns (standard)	two guns (standard)
Glass Bead Dispenser	NO	Optional	YES (standard)	NO (standard)
Net weight	58.0kgs	65.0kgs	153.7kgs	95.0kgs
Gross weight	114.0kgs	127.0kgs	234.8kgs	132kgs
Package size	103x70x80cm	103x70x80cm	160x110x123cm	110x75x92cm

Hydraulic Road Line Striper

LC line marker is heavy duty designed with high production features and bead capability for high performance striping on the most demanding jobs like large parking lots, airports, and city jobs that require precise lines and reflective beads.

Includes:
3/8"x15M high pressure hose, 2*1/4"x1M whip hose
2*X-450 spray gun, 2*1908 line marking tip and
3/8"to 1/4" connector and manuals.




DP-LC880

Large Oil Tank For Better Cooling
The improved bigger size oil tank which contains of 13L hydraulic oil inside, The more oil inside, the less temperature machine is operating and less wearing for the spare parts.



Superior Bead Application Performance
Ensures proper bead flow and paint penetration, Bead tanks(13L capacity) can be filled up continuously

- High Quality Oil Pump**
The imported oil pump is trouble free which makes sure the durability
- Direct-connected Engine**
The direct-connected engine gets no belt with higher transmission efficiency and lower consumpton
- Contractor preferred Honda GX engine**
Excellent power and proven reliability
- Easy Gun Adjustments**
Perfect gun alignment every time with easy-to-use guide mark system
- Large Pneumatic Tyre**
For easy moving in the job site and travel over rough surfaces.



Easy Handlebar Adjustment & Quality solenoid driven system
Simple front wheel alignment, no special tools needed.



Laser Guiding System
With less vibration and easy adjustment

2-Componets Hydraulic Road Line Striper

- Proven durable Piston Pump with Long-life V-packings,and stainless piston rod.
- Easy operate, easy control, and easy turn in any direction.
- Fluid section has slower-stroking piston, slower cycle rate and larger displacement for longer performance life.
- Ideal for most low to medium viscosity, waterborne traffic paints.
- Versatile gun bracket can be positioned to spray on left, right, front or rear of striper.
- Ideal fro small to medium-size line marking projects on athletic fields and pavement, parking lots, roads marking etc.



DP-LC880TD
4 G uns 2 Lines With Glass Beads



Glass Beads Device is Optional

Model No.	DP-LC880TD	
Engine power	9.0HP	
Max. pressure	228bar / 3306psi	
Max. flow rate	12L/min (3.17GPM)	
Guns	2 guns 1 line	4 guns 2 lines
	3 guns 3 lines	4 guns 4 lines

- Operator spraying controls are located right at the handle bars, designed for more comfortable and better control. You can fine tune the striping system operation without stopping
- Provides easier "up to the curb" parking lot striping ,and With the Front wheel LOCK system, you can also stripe arcs and curves in any angle.
- High-comfort handle-bar design for greater striper control and less operator fatigue
- Tall, low friction easy-roll wheels in big size, push easily for less operator fatigue.
- The valves are precised machined in stainless steel + tungsten carbide material for long life.

Ride-on Gas Line Striper



DP 6325LSP ONE GUN
DP 6335LSP TWO GUNS

Combined the electro-tricycle and the hand push line marker as the self-propelled line striper
Why walk if you can ride? double your pavement marking productivity with less investment.



Item No.	DP-6325LSP	DP-6335LSP
Type	Ride-on	Ride-on
Engine power	5.5HP(HONDA)	5.5HP (HONDA)
Max. pressure	210bar / 3045psi	210bar / 3045psi
Max. flow rate	2.0L/min (0.5GPM)	4.0L/min (1GPM)
Max. tip size	0.023" * 1gun	0.021" * 2guns
Guns	one gun (standard)	two guns (standard)
Max. operating speed	<40km/H (3 Speeds)	<40km/H (3 Speeds)
NW/GW(kgs)	288.5kgs	314.5kgs
Package size	170x85x113cm	170x85x113cm

Line Striper Booster

The booster connect to your striper to provide the most innovative, user-friendly ride-on systems available to double your striping productivity.



ZT-01
Driven by Gas




ZT-02
Driven by motor
Electricity by generator



Item No.	ZT-01	ZT-02
Driven	Honda engine	1000W Brushless Motor
Power	5.5HP	1.5HP Gasoline Generator
Max. operating speed	16km/H	30km/H
Max. reverse speed	10km/H	10km/H
NW/GW (kgs)	65/75	79/89
MEAS (cm)	140x70x100	120x72x85

Double diaphragm pump



Delivers stable output where constant material supply is required.
Fewer moving parts&simple structure ensures easy maintenance.
Ready to use after connecting to the air supply, hose&gun.
Flexible suction&return hoses for easy color change.



K17



K18



Main spare parts



Precious regulation valve assembly



K25



K40

Model No.	DP-K13	DP-K17	DP-K18	DP-K25	DP-K40	DP-K56	DP-K180
Fluid Input Size	3/8 inch	3/8 inch	3/8 inch	3/8 inch	1/2 inch	3/4 inch	1 inch
Max.Pressure	7bar / 101.5psi	7bar / 101.5psi	7bar / 101.5psi	7bar / 101.5psi	7bar / 101.5psi	7bar / 101.5psi	8bar / 116psi
Air Input Size	1/4"NPT	1/4"NPT	1/4"NPT	1/4"NPT	1/4"NPT	1/4"NPT	3/8"NPT
Starting Pressure	Planar Valve 1.6 bar	1.6 bar	1.6 bar	1.6 bar	1.6 bar	1.6 bar	1.6 bar
Low-Pressure Valve	0.5bar	0.5bar	0.5bar	0.5bar	0.5bar	0.5bar	0.7bar
Max.Prssage Amount	13L/Min (3.43GPM)	18L/Min (4.75GPM)	18L/Min (4.75GPM)	25L/Min (6.6GPM)	42L/Min (11GPM)	60L/Min (15.85GPM)	180L/min (47.55GPM)
Max.Air Consumption Capacity	150NL/Min	150NL/Min	150NL/Min	200NL/Min	350NL/Min	380NL/Min	960NL/Min
Particle Maximum Diameter	Φ2mm	Φ2mm	Φ2mm	Φ2mm	Φ3mm	Φ3mm	Φ6mm
Net Weight	7kgs	9kgs	8kgs	8.5kgs	9kgs	9kgs	9kgs
Carton Box Size	46*35*44cm	38*37*47cm	53.5*40*25cm	53.5*40*25cm	53.5*40*25cm	53.5*40*25cm	31*27*39cm

Double diaphragm pump



DP-K13



DP-K56



DP-K180



DP-6401 / 6402 / 6403

With Spray Gun & Hose
8L 10L 15L



DP-6411H/12H/13H/14H/16H

With S.S. Inner Tank
(Hand Mix-10L 20L 30L 40L 60L)



DP-K25M With Mixer



PR-5B



DP-W101

Optional for Fine Finish
with DD pumps.



DP-6411A/12A/13A/14A/16A With S.S. Inner Tank
(AIR Mix-10L 20L 30L 40L 60L)



Fluid Regulator



WJ-JT



WK-CT



WK-GS
Surge Tank

Model	PR-5B	WK-JT	WK-CT
Material	304 S.S.	304 S.S.	304 S.S.
Max.Pressure	250 Bar/ 3625Psi	250 Bar/ 3625Psi	250 Bar/ 3625Psi
Fluid Input size	G3/8" NPT	G1/4" NPT	G1/4" NPT
Fluid export size	G1/4" NPT	G1/4" NPT	G1/4" NPT
Max. delivery volume	2L/min	2L/min	3L/min
Pressure Ratio	1:1	4:1	1:1
Weight	0.9kgs	0.5kgs	0.4kgs

Model	WK-GS
Material	304 S.S.
Max.WPR	350Bar / 5000Psi
Fluid Input size	G3/8"NPT
Fluid export size	G1/4" NPT
Filter(M)	60/100/150/200
Weight	1.2kg

Stainless Steel Paint Tank



Stainless Steel Tank
SS-3 SS-5 SS-10 SS-20
3L 5L 10L 20L



Stainless Steel Tank With Mixer & DD Pump
SS-10M SS-10MD
10L 10L

Model No.	DP-6401	DP-6402	DP-6403	DP-6411H	DP-6411A
Tank Volume	8L	10L	15L	10L	10L
Agitator Type	NONE	NONE	NONE	Manual Agitator	Air Agitator
Outer Surface Treatment	Galvanized & Powder Coating	Galvanized & Powder Coating	Galvanized & Powder Coating	Powder Coating	Powder Coating
Inner Surface Treatment	Teflon Finishing	Teflon Finishing	Teflon Finishing	Powder Coating	Powder Coating
Stainless Steel inner tank Dimension (Diameter X Height)	NONE	NONE	NONE	Φ22cm X 28cm	Φ22cm X 28cm
Spraying Pressure	1-3.5bar	1-3.5bar	1-3.5bar	1-5bar	1-5bar
Release Pressure	4.5bar	4.5bar	4.5bar	5.5bar	5.5bar
Air Inlet Connector	1/4"	1/4"	1/4"	1/4"	1/4"
Paint Outlet Connector	3/8"	3/8"	3/8"	1/4"	1/4"
Tank Outer Dimension (Diameter X Height)	Φ24cm X 26cm	Φ24cm X 29cm	Φ24cm X 35cm	Φ24cm X 33cm	Φ24cm X 33cm
Agitator Motor Power	NONE	NONE	NONE	NONE	1/4HP
Contents in Package	1. paint tank 2. spray gun 3. 3.5m hose 4. pressure gauge 5. regulator 6. safety valve 7. on-off ball valve 8. manual, etc."	1. paint tank 2. spray gun 3. 3.5m hose 4. pressure gauge 5. regulator 6. safety valve 7. on-off ball valve 8. manual, etc."	1. paint tank 2. spray gun 3. 3.5m hose 4. pressure gauge 5. regulator 6. safety valve 7. on-off ball valve 8. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."


Model No.	DP-6412H	DP-6412A	DP-6413H	DP-6413A
Tank Volume	20L	20L	30L	30L
Agitator Type	Manual Agitator	Air Agitator	Manual Agitator	Air Agitator
Outer Surface Treatment	Powder Coating	Powder Coating	Powder Coating	Powder Coating
Inner Surface Treatment	Powder Coating	Powder Coating	Powder Coating	Powder Coating
Stainless Steel inner tank Dimension (Diameter X Height)	Φ30cm X 30cm	Φ30cm X 30cm	Φ30cm X 40cm	Φ30cm X 40cm
Spraying Pressure	1-5bar	1-5bar	1-5bar	1-5bar
Release Pressure	5.5bar	5.5bar	5.5bar	5.5bar
Air Inlet Connector	1/4"	1/4"	1/4"	1/4"
Paint Outlet Connector	1/4"	1/4"	1/4"	1/4"
Tank Outer Dimension (Diameter X Height)	Φ31.8cm X 34cm	Φ31.8cm X 34cm	Φ31.8cm X 41cm	Φ31.8cm X 41cm
Agitator Motor Power	NONE	1/4HP	NONE	1/4HP
Contents in Package	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."

Model No.	DP-6414H	DP-6414A	DP-6416H	DP-6416A
Tank Volume	40L	40L	60L	60L
Agitator Type	Manual Agitator	Air Agitator	Manual Agitator	Air Agitator
Outer Surface Treatment	Powder Coating	Powder Coating	Powder Coating	Powder Coating
Inner Surface Treatment	Powder Coating	Powder Coating	Powder Coating	Powder Coating
Stainless Steel inner tank Dimension (Diameter X Height)	Φ35cm X 35cm	Φ35cm X 35cm	Φ35cm X 50cm	Φ35cm X 50cm
Spraying Pressure	1-5bar	1-5bar	1-5bar	1-5bar
Release Pressure	5.5bar	5.5bar	5.5bar	5.5bar
Air Inlet Connector	1/4"	1/4"	1/4"	1/4"
Paint Outlet Connector	1/4"	1/4"	1/4"	1/4"
Tank Outer Dimension (Diameter X Height)	Φ38cm X 40cm	Φ38cm X 40cm	Φ38cm X 55cm	Φ38cm X 55cm
Agitator Motor Power	NONE	1/4HP	NONE	1/4HP
Contents in Package	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."	1. paint tank 2. pressure gauge 3. regulator 4. CE safety valve 5. on-off ball valve 6. manual, etc."

Pneumatic Mixer



Hand-held Type



Nylon

Alu.

Alu. & Nylon & Stainless Steel Blade



Clamped Type



Lift Type



Stationary Type

Handheld, Clamping & Stationary Type Air Agitator

Model No.	PM201A	PM201B	PM202A	PM202B	PM203A	PM203B	PM204A	PM204B	PM205A	PM208B
Description	Air Motor		Hand-Held		Easy Lift		Stationery		Clamping Type	
Motor Power	1/4HP	1/2HP	1/4HP	1/2HP	1/4HP	1/2HP	1/4HP	1/2HP	1/4HP	1/2HP
Free Load Speed	0-2000rpm	0-1000rpm	0-2000rpm	0-1000rpm	0-2000rpm	0-1000rpm	0-2000rpm	0-100rpm	0-2000rpm	0-1000rpm
Air Consumption	/		260L/min		260L/min		260L/min		260L/min	
Tank Capacity	/		10gal		10gal		5gal		50gal	
Axis Dimension	12mm		12mm		12mm		12mm		12mm	
Impeller Size	/		105mm		105mm		105mm		160mm	



DP-FA25 For Polyurethane Foam
DP-FA65 For Polyurea



Application: Polyurethane foam, 2-components spray, spouting, heat insulation, Foam insulate packing, PU foam filling jobs, Tank and pipe coating, Roof insulation.



For spraying



For injection



DP-FA50/FA60

Item No.	DP-FA25	DP-FA65	DP-FA50	DP-FA60
Air Supply	0.9MPa 1m³/min	0.9MPa 1m³/min	0.9MPa 1m³/min	0.9MPa 1m³/min
Application	Polyurethane	Polyurethane & Polyurea	Polyurethane	Polyurethane & Polyurea
Mixing ratio	1:1	1:1	1:1	1:1
Max. working pressure	110bar/1595psi	250bar/3625psi	200bar/2900psi	200bar/2900psi
Output volume	2~12Kg/min	2~12Kg/min	9kgs/min	9kgs/min
Max. hose length	90M	120M	90M	90M
Heating temperature	0~80 ℃	0~80 ℃	0~80 ℃	0~90 ℃
Net weight	139kgs	170kgs	197kgs	197kgs
Gross weight	224kgs	240kgs	244kgs	244kgs
Dimensions	97x78x160cm	86.5x80x148cm	90x90x148cm	90x90x148cm



HXP30



Fusion Type Gun

- Accurate temperature control and easy monitoring for result in good quality of spraying polyurea or Polyurethane material.
- Easy operating, easy cleaning, easy moving, high productivity polyurea or Polyurethane sprayer machine.
- User friendly machine's control board which indicate all the data of the heating temperature, pressure, and digital volume meter for easy monitoring of the A+B two components volume.



HXP20



Polyurea
spray gun



HXP20B
(Mixing ratio adjustable)

Model No.	DP-HXP20	DP-HXP20B	DP-HXP30	DP-FA60
Drive	Hydraulic-driven	Hydraulic-driven	Hydraulic-driven	Air-driven
Voltage	3-ph 380V 50h	3-ph 380V 50h	3-ph 380V 50h	3-ph 380V 50hz or 220v 50hz
Mixing volumetric ratio	1:1	1:1 to 1:3	1:1	1:1 or 1:2
Max. pressure	240bar / 3480psi	240bar / 3480psi	200bar / 2900psi	200bar / 2900psi
Max. output volume	9kgs/min (20 lbs/min)	9kgs/min (20 lbs/min)	10kgs/min (23 lbs/min)	9.5kgs/min (21lbs/min)
Heater power(watt)	11000-15000w	11000-15000w	20400w	16000w
Heating temperature	0-90℃ (194°F)	0-90℃ (194°F)	0-88℃ (190°F)	0-90℃ (194°F)
Max. hose length	90m (295ft)	90m (295ft)	90m (295ft)	90m (295ft)

Putty / Plaster/Texture Electric Rotor Stator Sprayer

For Heavy Material
Machine-based application of plaster and other heavy materials



T2



T5



T7



T7L



T9



T10



T20



T30

- Powerful performance spraying up to 30L/mins with hose lengths up to 50M
- Rotor stator technology handles aggregate materials up to 6 mm with ease
- Sprays fibered, aggregate and water-based materials (no solvent-based coatings can be applied)
- Up to 70L hopper allows for more spraying and less refilling
- Portable footprint designed to fit on standard scaffolding
- Automatic pressure delivers a better finish
- Quick and easy clean-up

Item No.	T2	T5	T7
Pump	Screw Pump	Screw Pump	Screw Pump
Power requirements	220/50Hz, 20A	220/50Hz, 20A	220/50Hz, 25A
Motor power	1500W Brushless DC	2200W Brushless DC	2800W Brushless DC
Flow rate	12.0L/MIN	15.0L/MIN	18.0L/MIN
Hopper capacity	30L	40L	40L
Max.Working pressure	20bar/290psi	20bar/290psi	30bar/435psi
Pumping height	10M	15M	20M
N/G Weight	28/47kgs	42/70.3.5kgs	54/82.5kgs
Package	Plywood Box(58.8*46.5*80cm)	Plywood Box(85*56*82cm)	Plywood Box(106*53*73.5cm)

Item No.	T9	T10	T20	T30
Pump	Screw Pump	Screw Pump	Screw Pump	Screw Pump
Power requirements	220/50Hz, 30A	220/50Hz, 30A	220/50Hz, 30A	220/50Hz, 30A
Motor power	4000W Brushless DC	5000W Brushless DC	4000W Brushless DC	5000W Brushless DC
Flow rate	30.0L/MIN	30.0L/MIN	15.0L/MIN	30.0L/MIN
Hopper capacity	55L	70L	70L	70L
Max.Working pressure	50bar/725psi	50bar/725psi	120bar/1740psi	50bar/725psi
Pumping height	30M	30M	30M	50M
N/G Weight	70/100kgs	95/132.5kgs	105/145kgs	105/152kgs
Package	Plywood Box(112*58*83cm)	Plywood Box(122*56*93cm)	Plywood Box(142*56*93cm)	Plywood Box(120*74*113cm)

Putty | plaster | texture sprayer

Cement mortar sprayer


Cement mortar sprayer



- 1 KW motor&retarder: to drives the twister for material transportation.
- 25L material hopper: for material storage
- Control box: the core of the machine, to drive the motor, and air pump.
- 2.2KW Twin-piston air compressor with aluminum housing: offer enough air pressure for the atomization in the spray outlet.
- Spinning form twister&Screw Pump: the material will be transport to the outlet by the screw pump after the quick and even mixing by twister.
- Cart with four wheels; with high load bearing, resist pressure, solid drag link, multi directional wheels, easy transportation.

T1 Barrel Screw Pump

Brushless Motor (Waterproof)
DRO For pressure and voltage
Built-in stirring system
Easy carry handle
Weight is 18kgs!



Item No.	TX350	TX450
Pump	Peristaltic pump 220/50Hz, 16A	Peristaltic pump 220/50Hz, 25A
Power requirments	1200W Brushless DC	1800W Brushless DC
Flow rate	6.0L/MIN	8.0L/MIN
Hopper capacity	50L	50L
Max.Working pressure	55bar/800psi	55bar/800psi
Pumping height	20M	20M
N/G Weight	70/96kgs	72/106kgs
Package	Plywood Box(88*62*109cm)	Plywood Box(98*62*109cm)



Model No.	DP-TX150	DP-TX300
Power type	pneumatic	pneumatic
Delivering pressure	4bar / 58psi	4bar / 58psi
Delivering distance	7.5m (25ft)	7.5m (25ft)
Nozzle size	4, 6, 8, 10mm	4, 6, 8, 10mm
Max. grain size	3mm	3mm
Tank capacity	30L	60L
Feature	For texture	For texture



DP-N7
DP-N7D


N7
cement mortar sprayer (electrical)
N7D
cement mortar sprayer (diesel engine drive)

DP-N6

N6
cement mortar sprayer (electrical)
N6M
cement mortar sprayer with mixer
N6C
cement mortar sprayer with compressor
N6MC
cement mortar sprayer with mixer & compressor

DP-N3

N3
cement mortar sprayer (electrical)
N3M
cement mortar sprayer with mixer
N3C
cement mortar sprayer with compressor
N3MC
cement mortar sprayer with mixer & compressor



Model	N6C	N6MC	N7D	N7	N3C	N3M
Power (v/hz)	3phase 220 or 380v 50 or 60hz	3phase 220 or 380v 50 or 60hz	8.5hp (186F) Diesel engine	3phase 220 or 380v 50 or 60hz	3phase 220 or 380v 50 or 60hz	3phase 220 or 380v 50 or 60hz
Motor power	6/7.3HP 4.5/5.5kw	6/7.3HP 4.5/5.5kw	8.5hp (186F)	6/7.3HP 4.5/5.5kw	4.4/5.3hp 3.3/4 kw	4.4/5.3hp 3.3/4 kw
Output capacity	40L/min (40.6GPM)	40L/min (40.6GPM)	60L/min (16GPM)	50L/min (13.2GPM)	30L/min (8GPM)	30L/min (8GPM)
Max. pressure	40bar / 580psi	40bar / 580psi	30bar / 435psi	30bar / 435psi	30bar / 435psi	30bar / 435psi
Max. Delivery height	40m (131ft)	40m (131ft)	30m (98ft)	30m (98ft)	20m (66ft)	20m (66ft)
Max. Delivery distance	60m (197ft)	60m (197ft)	60m (197ft)	60m (197ft)	40m (131ft)	40m (131ft)
Max.Grain size	6mm	6mm	8mm	8mm	5mm	5mm
Nozzle size	Standard 4 nozzles included.Available size 8 / 10 / 12 / 14 / 16 / 20mm					
Hopper capacity	100 L	100 L	100L	100L	65L	65L
Mixer capacity	/	120 L	/	/	/	100(120) L
Mixer power	/	4HP 3kw	/	/	/	4HP 3000w
Feature	with compressor	with compressor & mixer	engine driven	electric drive	with compressor	with mixer

Electrostatic Powder/Liquid Coating Machine

Airless Accessories



EP500



EP660



G3 GUN

Excellent extraction rate, significantly reducing the amount of powder
One-touch buttons for quick get the best coating result for different complex shapes work pieces
New pulse plus the intelligent technologies generate static manner, maximizing the electrostatic effect
Advanced design make great contributes towards high powder covering ratio in spraying various of shapes of work pieces.
Distinctive design of three air ways in spraying gun guarantee to obtain good conditions of powder output and ideal layer quality
The control unit connection all using quick coupling way easy to use
Super quality with specially wheel.



EP800D



EP900S



EF 100 For Liquid



G6 GUN



G1 GUN

Model No.	DP-EP500	DP-EP610	DP-EP800D	DP-EP900S	DP-EF100
Mains input voltage	220V/110V	220V/110V	220V/110V	220V/110V	220V/110V
Operating frequency	50Hz /60Hz	50Hz /60Hz	50Hz /60Hz	50Hz /60Hz	50Hz /60Hz
Input power	50W	50W	50W	50W	50W
Nominal output voltage	0-100KV (adjustable)	0-100KV (adjustable)	0-100KV (adjustable)	0-100KV (adjustable)	15-60KV (adjustable)
Nominal output current	180UA(max)	180UA(max)	180UA(max)	180UA(max)	80UA(max)
Protection type	IP54	IP54	IP54	IP54	
Ambient temperature range	0°C - +40°C (+32°F - +104°F)				
Max. operating temperature	50°C				



EZ Gun Trigger and Trigger Lock The Smoothest, lightweight & Softest gun trigger ever in the market! Safety Lock could also be used for keeping the gun continuously spraying without pulling the trigger manually. Rugged&Solid Design Durable forged aluminum with stand sharsh work environments Polished&Aodized body is easy to clean Exclusive Needle Design Factory set needle no need adjustments Guaranteed for life against breakage The spring doesn't touch any fluid, prolong its lifetime



DP-450

Airless spray gun (max.250bar)
Built-in gun filter, swivel connector



X450 Gun Repair Kits
Factory set needle
5 minutes to exchange the repair kits



DP-6371



DP-6372



DP-680

Airless spray gun with tip & tip guardMax.270bar / 3920psi pressure
Inlet connector: 1/4" NPSM, 1/4"PT, M16*1.5Output connector: 11/16", 7/8"4-finger trigger
Anodized aluminium Forged gun body for light weight (0.58kgs)and highpressure .
Built-in airless filter could be easily replaced. (standard filterincluded is 100mesh yellow color)
With Auto-cleaning reverse airless tip.Swivel free inlet connector.

DP-600 High pressure airless spray gun
forged aluminum + quench / hardening
process7mm super big fluid passing way
without clog
Specially designed for putty l plaster
(max.350bar)

DP-690 High pressure airless spray gun
500bar(no filter inside)
forged aluminum + quench 1 hardening
process bodyfor pneumatic driven airless
pump (max.500bar)



DP-600

Color available: Gold, Blue, Red,
Chrome coating etc.




DP-690

DP-6375L Straight handle airless spray gunwith swivel outlet, with tip & tin guardWith 50cm extension pole



Max.270bar / 3900psi pressure
Inlet connector: 1/4"NPSM, 1/4"PT, M16*1.5Output connector: 7/8"4- finger trigger
Built-in airless filter (standard is 60mesh white color)
Straight design reduce the hand fatigue for long time spraying,and easy spray to any angle.

DP-6375 Straight handle
airless spray gun
withswivel outlet, with
tip & tip guard



DP-6376 Silver Plus type airless spray gun (w/o filter inside)

Large fluid passing way for big painting project
Painting go through the tip nozzle directly, without touch to the needle or spring.Reduce the parts worn or rusting.
2-finger or 4-finger types are both available.Max.pressure: 345bar / 5000psiOutlet thread: 11/16" or 7/8".
Inlet connector: 1/4" NPSM, 1/4"PT, M16*1.5



DP-6376L Silver Plus type airless spray
gun (w/o filter inside)
with 50cm extension pole

Air-Mixed Airless Spray Gun Air-Assisted Airless Spray Gun



G40

Type of Feed: Pressure

Standard Nozzle:
0.43mm(517)Optional
nozzle: 0.28mm-
0.48mmOperating
pressure: 1000-
4000psiPatten width:
250-310mmPaint
distance: 30cm

Paint inlet connection:
1/4-NPSM or 1/4PT

500bar high pressure airless gun



High pressure
airless spray gun

Designed for pneumatic airless
paintsprayer (without filter
inside.)Max.pressure: 500bar 1
7250psiInlet connector: 1/4"NPSM,
1/4"PT,M16*1.5
Outlet thread: 7/8", 11/16",M16*1.5

AIRLESS SPRAY TIPS

DP-637XT

X Design Reversible Airless Spray Tip, Tip Gasket & Tip Guard Combo Kit
Stainless steel shank + Tungsten carbide orifice
Nylon + stainless steel tip gasket, Durable and easily reversed for cleaning.
Tip Shank Diameter: 11.1mm
Max.5000 PSI (345BAR)

DP-637LPT

SPRAYS AT LOWER PRESSURE
EASY PREP AND CLEANUP
LONGER LIFE TIME
LESS OVERSPRAY

Orifice Size	Fan Width - Inches						
inch	2"-4"Fan	4"-6"Fan	6"-8"Fan	8"-10"Fan	10"-12"Fan	12"-14"Fan	16"-18"Fan
0.008"	108	208	308				
0.010"	110	210	310	410	510		
0.012"	112	212	312	412	512		
0.014"	114	214	314	414	514		
0.016"	116				516	616	
0.018"					518	618	
0.020					520	620	



DP-637S Safety guard / tip holder

Size: 7/8", 11/16"
Max. 5000 PSI (345 BAR)



(For graco RAC X tips) 11/16" 7/8"



637S



Reversible Airless tips & tip gasket combo kitStainless steel shank + Tungsten carbide orifice
Nylon + stainless steel tip gasket, Durable and easily reversed for cleaning.Tip Shank Diameter: 11.1mmMax.5000 PSI (345 BAR)
This tip could fit Titan, Wagner, ASM, Airlessco etc.Most kind of airless guns. Guaranteed perfect quality, fine atomization. Over 5000 m2 lifetime.Tip size available: from 0.011" to 0.035" (2xx to 6xx)Best quality, best selling.

Reversible Airless tips & tip gasket combo kitAirless tip in RAC V type, used for old Graco guns.Stainless steel shank + Tungsten carbide orificeNylon + stainless steel tip gasket, Durableand easily reversed for cleaning.Tip Shank Diameter: 11.1mmMax.5000 PSI (345 BAR)
Tip size available: from 0.011" to 0.035" (2xx to 8xx)

Reversible Airless tips & tip gasket combo kit
Airless tip in RAC X type, used for new Graco contractor guns.Stainless steel shank + Tungsten carbide orifice
New material tip gasket, for easily reversed for cleaning.Tip Shank Diameter: 11 4mmMax.5000 PSI (345 BAR)
Guaranteed perfect quality, fine atomization. Over 5000 m2 lifetime.Tip size available: from 0.011" to 0.035" (2xx to 6xx)

LineLaser road marking tips
1708&1908 with width 14cm specially for road line marking
Creates clean, laser-sharp lines with no fuzzy edges or thin spots
Designed specifically for parking lots, roads, warehouse floors, crosswalksand athletic fields
Ensures consistent paint thickness, from edge to edge, less overspray and long-lasting lines Sprays heavy water-base to thin alkyd traffic paints



DP-637TW



DP-637XHD
500bar

Chart for airless tips

Orifice Size	Fan Width - Inches										Flow Rate		Application	Filter
inch	2" -4" Fan	4" -6" Fan	6" -8" Fan	8" -10" Fan	10" -12" Fan	12" -14" Fan	16" -18" Fan	24" -26" Fan	4" -6" Fan		gpm	L/min		
0.011"	111	211	311	411							0.12	0.45	Stain or Lacquer	150mesh (red)
0.013"	113	213	313	413	513	613					0.18	0.68		
0.015"	115	215	315	415	515	615					0.24	0.91	Oil Base Paint	100mesh (yellow)
0.017"	117	217	317	417	517	617			1708		0.31	1.17		
0.019"	119	219	319	419	519	619	819	1219	1908		0.38	1.44	Latex Paint / Acrylic / Enamel	100mesh (yellow)
0.021"	121	221	321	421	521	621	821	1221			0.47	1.78		
0.023"		223	323	423	523	623	823	1223			0.57	2.16	Heavy latex	60mesh (white)
0.025"		225	325	425	525	625	825	1225			0.67	2.54		
0.027"		227	327	427	527	627	827	1227			0.77	2.91	Elastomeric / Blockfiller / Primer	30mesh (green)
0.029"		229	329	429	529	629	829	1229			0.9	3.41		
0.031"		231	331	431	531	631	831	1231			1.03	3.9		
0.033"		233	333	433	533	633	833	1233			1.17	4.43		
0.035"		235	335	435	535	635	835	1235			1.31	4.96		
		237	337	437	537	637					3.41			
		239	339	439	539	639					3.9			
		241	341	441	541	641					4.43			
		243	343	443	543	643					4.96			
				445	545	645					3.41			
				447	547	647					3.9			
				449	549	649					4.43			
				451	551	651					4.96			
				453	553	653					4.43			
				455	555	655					4.96			

Example: For a tip with a .017" orifice and a 10" - 12" fan pattern, order DP637T-517 Reversible Tip. Fan width of a spray pattern is measured at 12" from the surface.



DP-637TT



DP-637T5



DP-637TX



DP-637TL



Blister Package

AIRLESS FILTERS



637FM

DP-637FM Airless filter for pump manifold
Size: 27mm diameter, 144mm height
Filter with wing: Fit Graco / Airlessco / Asturo etc.
Filter without wing: Fit Larius, Titan, etc.
DP-637FM30 30 mesh (637FM30W without wing)
DP-637FM60 60 mesh (637FM60W without wing)
DP-637FM100 100 mesh (637FM100W without wing)



637FT

DP-637FT Airless filter for pump manifold
Size: 27mm diameter, 72mm height
Filter Fit Graco / Larius etc.
DP-637FT30 30 mesh
DP-637FT60 60 mesh
DP-637FT100 100 mesh
DP-637FT150 150 mesh



637FB

DP-637FB Airless manifold filter for Graco pumps
Size: 20.6mm diameter , 91mm height
DP-637FB60 black (60 mesh)
DP-637FB100 blue (100 mesh)



637FB2

DP-637FB2 Airless manifold filter for Graco pumps
Size: 31.0mm diameter , 110mm&180mm height
DP-637FB60 black (60 mesh)
DP-637FB100 blue (100 mesh)



DP-637SF

DP-637SF Suction filter
Size: 3/4", 1", 1-1/4",
One-layer or Two-layers are available.

Airless Parts Accessories

Airless filters for spray gun
Stainless steel + welded
(A. Plug-in type, B. Thread screw-in type)

DP-637F150 red (150 mesh)
(Suitable for tip size: 0.009", 0.011", 0.013")

DP-637F180 red (180 mesh)
(Suitable for tip size: 0.009", 0.011", 0.013")

Airless filters for spray gun
Stainless steel + welded
(A. Plug-in type, B. Thread screw-in type)

DP-637F100 yellow (100 mesh)

Airless filters for spray gun
Stainless steel + welded
(A. Plug-in type, B. Thread screw-in type)

DP-637F60 white (60 mesh)
(Suitable for tip size: 0.019", 0.021", 0.023", 0.027")

DP-637F80 white (80 mesh)

Airless filters for spray gun
Stainless steel + welded
(A. Plug-in type, B. Thread screw-in type)

DP-637F30 Green (30 mesh)
(Suitable for tip size: 0.027", 0.029", 0.031", 0.033")

DP-637FG Airless filter for Graco guns
Size: 7.3mm diameter , 111.5mm height
DP-637FG60 black (60 mesh)
DP-637FG100 blue (100 mesh)



637F
637FG



Stainless steel + welded

A. Plug-in type,
B. Thread screw-in type

DP-637F30 #
Green (30 mesh)

DP-637F60 #
white (60 mesh)

DP-637F80 #
white (80 mesh)

DP-637F100 #
yellow (100 mesh)

DP-637F150 #
red (150 mesh)

DP-637F180 #
red (180 mesh)





DP-637LT
Extension pole for airless spray gun
(Aluminium material)

- DP-637LT15 15cm extension pole
- DP-637LT30 30cm extension pole
- DP-637LT50 50cm extension pole
- DP-637LT75 75cm extension pole
- DP-637LT100 100cm extension pole
- DP-637LT150 150cm extension pole



DP-637LS
Extension pole with swivel safety guard
(tip not included)

- DP-637LS15 15cm extension pole with swivel safety guard
- DP-637LS30 30cm extension pole with swivel safety guard
- DP-637LS50 50cm extension pole with swivel safety guard
- DP-637LS75 75cm extension pole with swivel safety guard
- DP-637LS100 100cm extension pole with swivel safety guard



DP-637LG
Extension pole with safety guard
(tip not included)

- DP-637LG15 15cm extension pole with safety guard
- DP-637LG30 30cm extension pole with safety guard
- DP-637LG50 50cm extension pole with safety guard
- DP-637LG75 75cm extension pole with safety guard
- DP-637LG100 100cm extension pole with safety guard



DP-637PR
Paint Roller (for airless sprayer)

With extra long tube (150cm) for high rolling jobs
Ideal for refinishing your house.
Recommend to connect with DP6375 straight-hand
airless spray gun

Airless Parts Accessories



637H
DP-637H01
1/4"*15M



DP-637H03
3/8"*15M

2-layers WIRE braided (Standard SAE100 R7)

Model	Size	Diameter (in*out)	Working pressure		Bursting pressure	
			Bar	psi	Bar	Psi
637H01	1/4"	6.3X13.3	400	5800	1450	21000
637H02	5/16"	7.9X14.9	380	5500	1300	18850
637H03	3/8"	9.5X16.7	350	5070	1160	17400
637H04	1/2 "	12.7X19.8	310	4490	1050	15900

2-layers FIBRE braided (Standard SAE100 R7)

Model	Size	Diameter (in*out)	Working pressure		Bursting pressure	
			Bar	psi	Bar	Psi
637H05	1/4"	6.3X12.7	340	4930	1360	19270
637H06	5/16"	7.9X115.0	310	4495	1240	17980
637H07	3/8"	9.5X18	250	3625	1000	14500
637H08	1/2 "	12.7X21.6	220	3190	880	12760

DP-637H High pressure airless painting hose (with spring protected at both ends)

Material: nylon inner tube, Polyurthane covered.Color: Blue, Red, Yellow, Black
The hose is conductive (static free)UL approved.



Sc01 Swivel Connector
Full stainless steel, Ball bearing structure, rotate flexibly.
Size: 1/4"*1/4", 3/8"*3/8", 1/4"*3/8 NPSM
All available in female or male end.



DP-637SP
Swivel free connector for extension poleSize: 7/8", or11/16"Max.pressure: 250bar



DP-637CS
Swivel free connector for airless gun or machine
Size: 1/4"*1/4", 3/8"*3/8", 1/4"*3/8" etc.Thread in BSP, PT, NPSM, and Metric size

DP-637C Hose Connector
Size: 1/4"*1/4", 3/8"*3/8", 1/4"*3/8" etc.Thread in BSP, PT, NPSM, and Metric sizeMaterial: steel



DRYWALL FINISHING TOOLS & ACCESSORIES

Smoothing Blades

The WBS series professional skimming blades are designed for a superior finish. The high-quality, ergonomic tools needed to deliver a perfect finish on any smoothing job with considerably less effort! There are 7 lengths available: 15cm, 25cm, 35cm, 45cm, 60cm, 80cm and 100cm.



Precision aluminum skimming blades
Delivers the smoothest finish, virtually eliminating sanding

Precise pivot point
integrated into the handle grip area

Ergonomic design
Requires less effort than standard knives for less fatigue and greater productivity

Composite blade handles
Lightweight composite for all-day comfort. Delivers a lighter and warmer experience than other heavy, cold metal designs


Flex Blade
Keeps the material on the work surface and off the blade, thereby minimising waste and the need for cleaning. Rounded edges for perfect smoothing

Flexes to provide more pressure and finishing area. Up to 10 times more contact area with the surface



Attaches to blades in seconds

Extendable design to reach anywhere



35CM/45CM/80CM Smoothing Kit

Aluminium Stilts



DP-ST4864

Name: 48" -64" aluminium stilts
Adjustable height: 48" - 64"
Load limit: 225LBS
Package: carton box
N.W: 10.5KGS
G.W: 11.5KGS
Dimension: 32*23*128CM




DP-ST1523

Name: 15" -23" aluminium stilts
Adjustable height: 15" - 23"
Load limit: 225LBS
Package: carton box
N.W: 5.7KGS
G.W: 6.3KGS
Dimension: 31*21*58CM



DP-ST2440

Name: 24" -40" aluminium stilts
Adjustable height: 24" - 40"
Load limit: 225LBS
Package: carton box
N.W: 7.0KGS
G.W: 8.0KGS
Dimension: 31*21*76CM



Plaster box PB-10

Wall Smoothen Board WSB-20

- * Smooth roller design for easy mounting on the wall surface
- * The pressure of the top head is adjustable for apply different surface shape or corner
- * The degree of the plaster box and bar is adjustable
- * The degree between work surface and bar is adjustable & locked.
- * Telescope design to meet different length

*Width: 40 / 45 / 50 / 60cm
*Length adjustable from 1.3 to 2.4 / 3.6 / 5 / 6m

Spray Guide Painting Tool



Quickly cut-in around windows, doors and roof lines with the ability to cover 30 feet in just 15 seconds
Eliminates time consuming masking or cutting in with a brush
Attaches to an extension pole decreasing ladder work
Unique freewheeling disc glides smoothly over virtually every surface

DP-637SPT Spray Guide Painting Tool

Hopper Gun can be used for applying plaster, hard coat stucco, EIFS, small scale shotcrete, papercrete, arthen mixes etc.
Hopper: 304 stainless steel.
Valve: 100% high quality brass, 1/2" female swivel 1/4" air plug with 3/8" NPT male.



DP-CH100A

HVLP Turbine Paint Sprayer



Power: 1400W.
Standard motor: 2 stage.
(3-stage is available also).
Paint sprayer type: HVLP
Operating pressure: 4-6 psi.
Fluid Delivery Volume: 0.3L/min.
Hose Length: 7.5M.
Tip nozzle size: 1.0/1.3/1.5MM.



TABLE OF CONTENTS



DIY Airless Paint Sprayers

1~4



Electric Paint Sprayers-Piston pump

5~22



Electric Paint Sprayers-Diaphragm Pump

23~26



Air Powered Paint Sprayers

27~30



Gas Powered Paint Sprayers & Hydraulic Pump

31~36



Line Marking Machine & Booster

37~42



AODD/Double Diaphragm Pump

43~45



Pressure Tank/Pots & Air Agitator

46~48



Polyurethane Foam/Polyurea Sprayer

49~50



Texture/Plaster/Cement Sprayers

51~54



Electrostatic Coating Equipment

55



Airless Gun/Tip/Filter/Hose

55~64



Drywall Tools & Others

65-67