



X-450 are designed to be the longest lasting, most reliable airless spray guns in the market. Its durability, long life, spray performance and comfortable design are the best choice of painting contractors.

Specifications

Max. operating pressure

- 250Bar (3600 PSI)

Material inlet thread size

- NPSM 1/4" - PT 1/4"-(M16 x1.5)

Diffuser thread size

- 7/8" - 11/16" -

Wetted parts material

- High-grade stainless steel, aluminum, PTFE, Tungsten Carbide

Operating temperature range

- 5°C to 40°C (40°F to 104°F)

Maximum material temperature:

- 43°C (109°F)

Package: Color box or Double Blister

- Color: Silver as standard
Or Gold/Blue/Red/Black...Optional

Application

- Both Water-based & Oil Based

- Weight: 460 g (1.0 Lb)



Features

Rugged & Solid Design

Durable forged aluminum withstands

harsh work environments

Polished & Aodized body is easy to clean

Exclusive Needle Design

Factory set needle no need adjustments

Guaranteed for life against breakage

The spring doesn't touch any fluid, prolong its lifetime



Gun Repair Kits
Factory set needle
5 minutes to exchange
the repair kits

EZ Out Gun Filter

Filters from the inside out to prevent filter from collapsing

Interchangeable with DP-6371 spray gun.

EZ Glide Swivel

Unique design reduces sealing friction under pressure,
making this the best swivel on the market!

EZ Gun Trigger and Trigger Lock

The Smoothest, lightweight & Softest gun trigger ever in the market!

Safety Lock could also be used for keeping the gun continuous spraying without
pulling the trigger manually.

Ergonomic Design

Form-fitted handle provides maximum control and comfort

Detachable trigger guard swings clear of gun handle for easy filter access

Lightweight design reduces operator fatigue (Total 460g only with tip & guard)

Optional Accessories



The standard filter is 637F60
(White 60 mesh)

The Green-30mesh, Yellow-100mesh
and Red-150mesh are Optional



The standard inlet swivel is 637SG
(1/4" NPSM)

The size 1/4" PT, M16x1.5 are optional



The standard outlet connector
is 7/8"

The size 11/16" are optional